Crop Smalt better crop protection

Smart Select Maxi-P +

Crop Smart Pty Ltd

Chemwatch Hazard Alert Code: 4 Issue Date: 16/07/2024

Version No: 3.1 Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements Issue Date: **16/07/2024** Print Date: **23/07/2024** S.GHS.AUS.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Chemwatch: 5669-34

Product name	Smart Select Maxi-P +	
Chemical Name	Not Applicable	
Synonyms	ot Available	
Proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S. (contains phosphoric acid)	
Chemical formula	Not Applicable	
Other means of identification	Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Foliar
Relevant luentineu uses	

Foliar Fertiliser for application in agriculture. Use according to manufacturer's directions.

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Crop Smart Pty Ltd	
Address	409/ 4 Daydream Street WARRIEWOOD NSW 2102 Australia	
Telephone	1 1300 783 481	
Fax	Not Available	
Website	www.cropsmart.com.au	
Email	Compliance@cropsmart.com.au	

Emergency telephone number

Association / Organisation	CHEMWATCH EMERGENCY RESPONSE (24/7)	
Emergency telephone numbers	+61 1800 951 288	
Other emergency telephone numbers	+61 3 9573 3188	

Once connected and if the message is not in your preferred language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	S6
Classification ^[1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1A, Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H302	Harmful if swallowed.	
H314	auses severe skin burns and eye damage.	
H412	Harmful to aquatic life with long lasting effects.	

Precautionary statement(s) Prevention

P260	Do not breathe mist/vapours/spray.	
P264	P264 Wash all exposed external body areas thoroughly after handling.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).		
P303+P361+P353	F ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P310	nmediately call a POISON CENTER/doctor/physician/first aider.		
P363	Wash contaminated clothing before reuse.		
P301+P312	IF SWALLOWED: Call a POISON CENTER/doctor/physician/first aider if you feel unwell.		
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

P501

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7664-38-2	73	phosphoric acid
10034-96-5	<1	manganese sulfate, hydrate
7446-19-7	<1	zinc sulfate monohydrate
7758-99-8	<1	copper sulfate, pentahydrate
10034-99-8	<1	magnesium sulfate, heptahydrate
7782-63-0	<1	ferrous sulfate heptahydrate
Not Available	<1	Ingredients determined not to be hazardous
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

	If this product comes in contact with the eyes:
Eye Contact	 Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

Observe the patient carefully.
 Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
 Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

for phosphate salts intoxication:

- All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.
- Ingestion of large quantities of phosphate salts (over 1.0 grams for an adult) may cause an osmotic catharsis resulting in diarrhoea and probable abdominal cramps. Larger doses such as 4-8 grams will almost certainly cause these effects in everyone. In healthy individuals most of the ingested salt will be excreted in the faeces with the diarrhoea and, thus, not cause any systemic toxicity. Doses greater than 10 grams hypothetically may cause systemic toxicity.
- Treatment should take into consideration both anionic and cation portion of the molecule.
 All phosphate salts, except calcium salts, have a hypothetical risk of hypocalcaemia, so calcium levels should be monitored.
- For acute or short term repeated exposures to strong acids:
- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues.

INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.
- SKIN:
- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.
 EYE:
- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.				
Advice for firefighters					
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Use fire fighting procedures suitable for surrounding area. Do not approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. Equipment should be thoroughly decontaminated after use. 				
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke. Decomposition may produce toxic fumes of: phosphorus oxides (POx) sulfur oxides (SOx) metal oxides 				
HAZCHEM	2X				

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

- Minor Spills Environmental hazard contain spillage.
 - Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.
 - Check regularly for spills and leaks.
 - Clean up all spills immediately.
 - Avoid breathing vapours and contact with skin and eyes.

	 Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite. Wipe up. Place in a suitable, labelled container for waste disposal.
Major Spills	 Environmental hazard - contain spillage. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course. Consider evacuation (or protect in place). Stop leak if safe to do so. Contain spill with sand, earth or vermiculite. Collect recoverable product into labelled containers for recycling. Neutralise/decontaminate residue (see Section 13 for specific agent). Collect solid residues and seal in labelled drums for disposal. Wash area and prevent runoff into drains. After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 DO NOT allow clothing wet with material to stay in contact with skin Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material. Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Keep containers securely sealed when not in use. Avoid physical damage to containers. Always wash hands with soap and water after handling. Work clothes should be laundered separately. Launder contaminated clothing before re-use. Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. Protect containers against physical damage and check regularly for leaks. Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Conditions for sale storage, in	cluding any incompatibilities
Suitable container	 Glass container is suitable for laboratory quantities DO NOT use aluminium or galvanised containers Check regularly for spills and leaks Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and Iow pressure tubes and cartridges may be used. Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.
Storage incompatibility	 Phosphoric acid: is a medium-strong acid which produces violent reaction with bases may produce violent react when water is added to the concentrated form reacts violently with solutions containing ammonia or bleach, azo compounds, epoxides and other polymerisable compounds reacts, possibly violently with amines, aldehydes, alkanolamines, alcohols, alkylene oxides, amides, ammonia, ammonia hydroxide, calcium oxide, cyanides, epichlorohydrin, esters, halogenated organics, isocyanates, ketones, oleum, organic anhydrides, sodium tetraborate, sulfides, sulfuric acid, strong oxidisers, vinyl acetate forms explosive mixtures with nitromethane at elevated temperatures does not attack stainless steel, copper or its alloys atroom temperature does not attack stainless steel, copper or its alloys attacks glass, ceramics, and some plastics, rubber and coatings Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0. Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts - neutralisation can generate dangerously large amounts of heat in small spaces. The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat. The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid. Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas. Inorganic acids react with cyanide compounds to release gaseous hydrogen cyanide.

	dithionites (SO2), and ever Acids often catalyse (incre- Reacts vigorously with alka Reacts with mild steel, galv Phosphates are incompatit Phosphates are susceptibl hydrides.	ng agents. Add n carbonates. ase the rate of) alis vanised steel / : ble with oxidisir le to formation o	itional gas-generating reaction chemical reactions. zinc producing hydrogen gas v	s occur with s which may for whosphine gas	m an e in the	s, nitrites, thi explosive mi e presence c	osulfates (to give kture with air. f strong reducing	H2S and SO3),
ECTION 8 Exposure contro	ols / personal protection							
ontrol parameters								
Occupational Exposure Limits	(OEL)							
INGREDIENT DATA	Ingredient	Material nar		TWA	ST	-1	Peak	Notes
Australia Exposure Standards	phosphoric acid	Phosphoric a		1 mg/m3	-	r⊈ ng/m3	Not Available	Not Available
Australia Exposure Standards	manganese sulfate, hydrate		dust & compounds (as Mn)	1 mg/m3		t Available	Not Available	Not Available
Australia Exposure Standards	ferrous sulfate heptahydrate	Iron salts, so	,	1 mg/m3		Available	Not Available	Not Available
		,						
Emergency Limits	TEEL-1		TEEL-2			TEEL-3		
Ingredient					_		-1-	
phosphoric acid	Not Available		Not Available			Not Availa	bie	
manganese sulfate, hydrate	9.2 mg/m3		15 mg/m3			90 mg/m3	-	
	8.2 mg/m3					430 mg/m	3	
			14 mg/m3		_	F00 / /	.	
zinc sulfate monohydrate	15 mg/m3		97 mg/m3			580 mg/m	3	
zinc sulfate monohydrate copper sulfate, pentahydrate	15 mg/m3 7.5 mg/m3		97 mg/m3 9.9 mg/m3			59 mg/m3		
zinc sulfate monohydrate copper sulfate, pentahydrate copper sulfate, pentahydrate	15 mg/m3		97 mg/m3					
zinc sulfate monohydrate copper sulfate, pentahydrate copper sulfate, pentahydrate magnesium sulfate,	15 mg/m3 7.5 mg/m3		97 mg/m3 9.9 mg/m3			59 mg/m3	3	
zinc sulfate monohydrate copper sulfate, pentahydrate copper sulfate, pentahydrate magnesium sulfate, heptahydrate magnesium sulfate,	15 mg/m3 7.5 mg/m3 12 mg/m3		97 mg/m3 9.9 mg/m3 32 mg/m3			59 mg/m3 190 mg/m3	3 n3	
manganese sulfate, hydrate zinc sulfate monohydrate copper sulfate, pentahydrate copper sulfate, pentahydrate magnesium sulfate, heptahydrate magnesium sulfate, heptahydrate ferrous sulfate heptahydrate	15 mg/m3 7.5 mg/m3 12 mg/m3 33 mg/m3		97 mg/m3 9.9 mg/m3 32 mg/m3 370 mg/m3			59 mg/m3 190 mg/m3 2,300 mg/m	3 n3 n3	

Ingredient	Original IDLH	Revised IDLH
phosphoric acid	1,000 mg/m3	Not Available
manganese sulfate, hydrate	500 mg/m3	Not Available
zinc sulfate monohydrate	Not Available	Not Available
copper sulfate, pentahydrate	Not Available	Not Available
magnesium sulfate, heptahydrate	Not Available	Not Available
ferrous sulfate heptahydrate	Not Available	Not Available

Occupational Exposure Banding					
Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit			
zinc sulfate monohydrate	E	≤ 0.01 mg/m³			
copper sulfate, pentahydrate	E	≤ 0.01 mg/m³			
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.				

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-desig can be highly effective in protecting workers and will typically be independent of worker interactions to provide this h The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant i design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure. Local exhaust ventilation usually required. If risk of overexposure exists, wear approved respirator. Correct fit is essential to ensure and An approved self contained breathing apparatus (SCBA) may be required in some situations. Provide adequate ventilation in warehouse or closed storage area. Air contaminants generated in the workplace pos velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the of	igh level of protection. I ventilation that f designed properly. Th ential to obtain adequa dequate protection. ssess varying "escape'
	Type of Contaminant:	Air Speed:
	Type of Contaminant: solvent, vapours, degreasing etc., evaporating from tank (in still air).	Air Speed: 0.25-0.5 m/s (50 100 f/min.)

direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active 1-2.5 m/s (200-500 f/min.) generation into zone of rapid air motion) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone 2.5-10 m/s (500of very high rapid air motion). 2000 f/min.) Within each range the appropriate value depends on: Lower end of the range Upper end of the range 1: Room air currents minimal or favourable to capture 1: Disturbing room air currents 2: Contaminants of low toxicity or of nuisance value only. 2: Contaminants of high toxicity 3: Intermittent, low production 3: High production, heavy use 4: Large hood or large air mass in motion 4: Small hood-local control only Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used. Individual protection measures, such as personal protective equipment Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eve protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure. Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS] 1337.1, EN166 or national equivalent] Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection. Alternatively a gas mask may replace splash goggles and face shields. Eye and face protection Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eve redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59]. Skin protection See Hand protection below Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: • The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended. Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include: frequency and duration of contact, chemical resistance of glove material, glove thickness and dexterity Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to Hands/feet protection EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. Contaminated gloves should be replaced. As defined in ASTM F-739-96 in any application, gloves are rated as: · Excellent when breakthrough time > 480 min Good when breakthrough time > 20 min Fair when breakthrough time < 20 min Poor when glove material degrades For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended. It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended **Body protection** See Other protection below Overalls. Other protection

- PVC Apron.
- PVC protective suit may be required if exposure severe.

Recommended material(s)

GLOVE SELECTION INDEX

generated selection:

Smart Select Maxi-P +

NAT+NEOPR+NITRILE

NATURAL+NEOPRENE

NEOPRENE/NATURAL

NATURAL RUBBER

Material

NEOPRENE

NITRILE+PVC

NITRILE

PE

PVC

Glove selection is based on a modified presentation of the:

The effect(s) of the following substance(s) are taken into account in the computer-

"Forsberg Clothing Performance Index"

Smart Select Maxi-P +

CPI

A

А

A

A

A

A

А

А

А

А

Eyewash unit.Ensure there is ready access to a safety shower.

Respiratory protection

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	B-AUS P2	-	B-PAPR-AUS / Class 1 P2
up to 50 x ES	-	B-AUS / Class 1 P2	-
up to 100 x ES	-	B-2 P2	B-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

 \cdot Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.

 The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
 Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.

 Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.

• Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)

Use approved positive flow mask if significant quantities of dust becomes airborne.
 Try to avoid creating dust conditions.

* CPI - Chemwatch Performance Index

A: Best Selection

SARANEX-23

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

 $\ensuremath{\text{NOTE}}$ As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Ansell Glove Selection

Glove — In order of recommendation
AlphaTec® Solvex® 37-675
AlphaTec 02-100
AlphaTec® Solvex® 37-185
AlphaTec® 58-008
AlphaTec® 58-530B
AlphaTec® 58-530W
AlphaTec® 58-735
AlphaTec® 79-700
AlphaTec® 38-612
DermaShield™ 73-711

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Lighter brown solution and a darker brown precipitate settled at the bottom; mixes with water.				
Physical state	Liquid	Relative density (Water = 1)	1.37		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available		
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available		
pH (as supplied)	<0.5	Decomposition temperature (°C)	Not Available		
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available		
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable		
Flash point (°C)	Not Available	Taste	Not Available		
Evaporation rate	Not Available	Explosive properties	Not Available		
Flammability	Not Available	Oxidising properties	Not Available		
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available		
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available		
Vapour pressure (kPa)	Not Available	Gas group	Not Available		

Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Contact with alkaline material liberates heat Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

ionnation on toxicological c				
Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of the vapour may cause choking, coughing, headache, weakness and dizziness, and with long term exposure, fluid accumulation in the lungs and blueness, initially in the fingertips. High concentrations cause inflamed airways and watery swelling of the lungs with oedema. There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs.			
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. There is strong evidence to suggest that this material can cause, if swallowed once, very serious, irreversible damage of organs. Ingesting large amounts of phosphoric acid may cause severe abdominal pain, thirst, acidaemia (excessive acid in the blood), breathing difficulties, convulsions, collapse, shock and death. It also has a corrosive effect if swallowed.			
Skin Contact	Skin contact with the material may be harmful; systemic effects may result following absorption. There is strong evidence to suggest that this material, on a single contact with skin, can cause very serious, irreversible damage of organs. Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.			
Eye	Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. If applied to the eyes, this material causes severe eye damage. Irritation of the eyes may produce a heavy secretion of tears (lachrymation).			
Chronic	Repeated or prolonged exposure to acids may result in the erosion of lung, with cough, and inflammation of lung tissue often occurs. Long-term exposure to respiratory irritants may result in airways disea Skin contact with the material is more likely to cause a sensitisation re- Ample evidence exists from experimentation that reduced human fertil Ample evidence exists, from results in experimentation, that developm	se, involving difficulty breathing and related whole-body problems. action in some persons compared to the general population. ity is directly caused by exposure to the material.		
	τοχιςιτγ	IRRITATION		
Smart Select Maxi-P +	Not Available	Not Available		
	ΤΟΧΙΟΙΤΥ	IRRITATION		
	Dermal (rabbit) LD50: >1260 mg/kg ^[2]	Eye (rabbit): 119 mg - SEVERE [Monsanto]*		
phosphoric acid	Inhalation (Rat) LC50: 0.026 mg/L4h ^[2]	Eye: adverse effect observed (irritating) ^[1]		
	Oral (Rat) LD50: 1530 mg/kg ^[2]	Skin (rabbit):595 mg/24h - SEVERE		
		Skin: adverse effect observed (corrosive) ^[1]		
	тохісіту	Skin: adverse effect observed (corrosive) ^[1] IRRITATION		
manganese sulfate, hydrate	TOXICITY Oral (Rat) LD50: 2150 mg/kg ^[2]			
manganese sulfate, hydrate		IRRITATION		
manganese sulfate, hydrate zinc sulfate monohydrate	Oral (Rat) LD50: 2150 mg/kg ^[2]	IRRITATION Skin: no adverse effect observed (not irritating) ^[1]		
	Oral (Rat) LD50: 2150 mg/kg ^[2] TOXICITY	IRRITATION Skin: no adverse effect observed (not irritating) ^[1] IRRITATION		
	Oral (Rat) LD50: 2150 mg/kg ^[2] TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1]	IRRITATION Skin: no adverse effect observed (not irritating) ^[1] IRRITATION Eye: adverse effect observed (irreversible damage) ^[1]		
	Oral (Rat) LD50: 2150 mg/kg ^[2] TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Oral (Mouse) LD50; 200 mg/kg ^[2]	IRRITATION Skin: no adverse effect observed (not irritating) ^[1] IRRITATION Eye: adverse effect observed (irreversible damage) ^[1] Skin: no adverse effect observed (not irritating) ^[1]		
zinc sulfate monohydrate	Oral (Rat) LD50: 2150 mg/kg ^[2] TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Oral (Mouse) LD50; 200 mg/kg ^[2] TOXICITY	IRRITATION Skin: no adverse effect observed (not irritating) ^[1] IRRITATION Eye: adverse effect observed (irreversible damage) ^[1] Skin: no adverse effect observed (not irritating) ^[1] IRRITATION IRRITATION		
zinc sulfate monohydrate	Oral (Rat) LD50: 2150 mg/kg ^[2] TOXICITY dermal (rat) LD50: >2000 mg/kg ^[1] Oral (Mouse) LD50; 200 mg/kg ^[2] TOXICITY dermal (rat) LD50: >2000 mg/kg ^[2]	IRRITATION Skin: no adverse effect observed (not irritating) ^[1] IRRITATION Eye: adverse effect observed (irreversible damage) ^[1] Skin: no adverse effect observed (not irritating) ^[1] IRRITATION IRRITATION		

Oral (Rat) LD50: >2000 mg/kg^[1] Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION Oral (Mouse) LD50; 1520 mg/kg^[2] Eye: adverse effect observed (irritating)^[1] ferrous sulfate heptahydrate Skin: adverse effect observed (irritating)^[1] 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise Legend: specified data extracted from RTECS - Register of Toxic Effect of chemical Substances phosphoric acid (85%) For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. PHOSPHORIC ACID Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production. MANGANESE SULFATE, Not available HYDRATE for copper and its compounds (typically copper chloride): Acute toxicity: There are no reliable acute oral toxicity results available. In an acute dermal toxicity study (OECD TG 402), one group of 5 male rats and 5 groups of 5 female rats received doses of 1000, 1500 and 2000 mg/kg bw via dermal application for 24 hours. The LD50 values of copper monochloride were 2,000 mg/kg bw or greater for male (no deaths observed) and 1,224 mg/kg bw for female. Four females died at both 1500 and 2000 mg/kg bw, and one at 1,000 mg/kg bw. Symptom of the hardness of skin, an exudation of hardness site, the formation of scar and reddish changes were observed on application sites in all treated animals. Skin inflammation and injury were also noted. In addition, a reddish or black urine was observed in females at 2,000, 1,500 and 1,000 mg/kg bw. Female rats appeared to be more sensitive than male based on mortality and clinical signs. No reliable skin/eye irritation studies were available. The acute dermal study with copper monochloride suggests that it has a potential to cause skin irritation Repeat dose toxicity: In repeated dose toxicity study performed according to OECD TG 422, copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39 - 51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL value was 5 and 1.3 mg/kg bw/day for male and female rats, respectively. No deaths were observed in male rats. One treatment-related death was observed in female rats in the high dose group. Erythropoietic toxicity (anaemia) was seen in both sexes at the 80 mg/kg bw/day. The frequency of squamous cell hyperplasia of the forestomach was increased in a dose-dependent manner in male and female rats at all treatment groups, and was statistically significant in males at doses of =20 mg/kg bw/day and in females at doses of =5 mg/kg bw/day doses. The observed effects are considered to be local, non-systemic effect on the forestomach which result from oral (gavage) administration of copper monochloride. Genotoxicity: An in vitro genotoxicity study with copper monochloride showed negative results in a bacterial reverse mutation test with COPPER SULFATE Salmonella typhimurium strains (TA 98, TA 100, TA 1535, and TA 1537) with and without S9 mix at concentrations of up to 1,000 ug/plate. An in vitro test for chromosome aberration in Chinese hamster lung (CHL) cells showed that copper monochloride induced structural and numerical aberrations at the concentration of 50, 70 and 100 ug/mL without S9 mix. In the presence of the metabolic activation system, PENTAHYDRATE significant increases of structural aberrations were observed at 50 and 70 ug/mL and significant increases of numerical aberrations were observed at 70 ug/mL. In an in vivo mammalian erythrocyte micronucleus assay, all animals dosed (15 - 60 mg/kg bw) with copper monochloride exhibited similar PCE/(PCE+NCE) ratios and MNPCE frequencies compared to those of the negative control animals. Therefore copper monochloride is not an in vivo mutagen. Carcinogenicity: there was insufficient information to evaluate the carcinogenic activity of copper monochloride. Reproductive and developmental toxicity: In the combined repeated dose toxicity study with the reproduction/developmental toxicity screening test (OECD TG 422), copper monochloride was given orally (gavage) to Sprague-Dawley rats for 30 days to males and for 39-51 days to females at concentrations of 0, 1.3, 5.0, 20, and 80 mg/kg bw/day. The NOAEL of copper monochloride for fertility toxicity was 80 mg/kg bw/day for the parental animals. No treatment-related effects were observed on the reproductive organs and the fertility parameters assessed. For developmental toxicity the NOAEL was 20 mg/kg bw/day. Three of 120 pups appeared to have icterus at birth; 4 of 120 pups appeared runted at the highest dose tested (80 mg/kg bw/day). For copper sulfate Copper sulfate is corrosive. Side effects are diverse and multi-systemic, and include severe gastrointestinal symptoms and signs, metallic taste in the mouth, burning pain in the chest, headache, sweating, shock and damage to brain, liver and kidneys. It has been reported as a cause of human suicide. On exposure, it can cause dose dependent damage to the skin and eye, also, eczema and allergic reactions. Long term effects can lead to anaemia and degenerative changes and are more likely in individuals with Wilson's disease, a condition which causes excessive absorption and storage of copper. It has adverse effects on reproduction and fertility as well as cancer and embryo toxic effects. Although it is excreted in the faeces, there is residual accumulation the liver, brain, heart, kidney and muscles, MAGNESIUM SULFATE, Oral (man) TDLo: 183 mg/kg/4h-I Nil reported HEPTAHYDRATE PHOSPHORIC ACID & ZINC No significant acute toxicological data identified in literature search. SULFATE MONOHYDRATE Acute Toxicity Carcinogenicity × Skin Irritation/Corrosion -Reproductivity × Serious Eye -× STOT - Single Exposure Damage/Irritation Respiratory or Skin × STOT - Repeated Exposure × sensitisation × Mutagenicity Aspiration Hazard 🗙 – Data either not available or does not fill the criteria for classification Legend: Data available to make classification

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)	Species	Value	Source
Smart Select Maxi-P +	Not Available	Not Available	Not Available	Not Available	Not Availab
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	EC50	72h	Algae or other aquatic plants	77.9mg/l	2
nheanharia acid	EC50	48h	Crustacea	>100mg/l	2
phosphoric acid	LC50	96h	Fish	67.94- 113.76mg/L	4
	NOEC(ECx)	72h	Algae or other aquatic plants	Algae or other aquatic plants <7.5mg/l	
	Endpoint	Test Duration (hr)	Species	Value	Sourc
	LC50	96h	Fish	130.465mg/l	4
	NOEC(ECx)	96h	Fish	84mg/L	5
	EC50	72h	Algae or other aquatic plants	61mg/l	2
manganese sulfate, hydrate	EC50	48h	Crustacea	7.09- 9.36mg/l	4
	LC50	96h	Fish	0.19- 12.49mg/l	4
	EC50	96h	Algae or other aquatic plants	25.7mg/L	4
	NOEC(ECx)	1440h	Crustacea	0.01mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Sour
	BCF	1344h	Fish	59-112	7
	EC50	72h	Algae or other aquatic plants	0.01- 0.122mg/l	4
zinc sulfate monohydrate	EC50	48h	Crustacea	Crustacea 0.06mg/L	
	LC50	96h	Fish	Fish <0.001mg/L	
	EC50	96h	Algae or other aquatic plants		
	EC20(ECx)	72h	Algae or other aquatic plants	Algae or other aquatic plants 0.001- 0.075mg/l	
	Endpoint	Test Duration (hr)	Species	Species Value	
	EC50	72h	Algae or other aquatic plants	0.8mg/L	Source 5
opper sulfate, pentahydrate	EC50	48h	Crustacea	0.003mg/L	5
opper suitate, pentanyutate	LC50	96h	Fish	0.073mg/L	4
	EC50(ECx)	96h	Crustacea	0.001mg/L	5
	Endneint	Test Duration (kr)	Species	Value	Cour
	Endpoint EC50	Test Duration (hr) 72h	Algae or other aquatic plants	2700mg/l	Sour 1
magnesium sulfate,	EC50	48h	Crustacea	266.4-	
heptahydrate	LC50	96h	Fish	33_	
	EC0(ECx)	72h	Algae or other aquatic plants		
	Endpoint	Test Duration (hr)	Species	Value	Sour
	EC50	48h	Crustacea	12.35-	4
errous sulfate heptahydrate	LC50	96h	Fish	16.72mg/L Fish 6.27-	
	EC50(ECx)	48h	Crustacea	12.35-	4
Legend:	EC50(ECx)	48h 1. IUCLID Toxicity Data 2. Europe E		16.72mg/L nation - Aquatic Toxicity	4.

Toxic to aquatic organisms.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

On the basis of available evidence concerning either toxicity, persistence, potential to accumulate and or observed environmental fate and behaviour, the material may present a danger, immediate or long-term and /or delayed, to the structure and/ or functioning of natural ecosystems.

Ecotoxicity: The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

For Phosphate: The principal problems of phosphate contamination of the environment relates to eutrophication processes in lakes and ponds. Phosphorus is an essential plant nutrient and is usually the limiting nutrient for blue-green algae.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Aquatic Fate: Lakes overloaded with phosphates is the primary catalyst for the rapid growth of algae in surface waters. Planktonic algae cause turbidity and flotation films. Shore algae cause ugly muddying, films and damage to reeds. Decay of these algae causes oxygen depletion in the deep water and shallow water near the shore. The process is self-perpetuating because an anoxic condition at the sediment/water interface causes the release of more adsorbed phosphates from the sediment. The growth of algae produces undesirable effects on the treatment of water for drinking purposes, on fisheries, and on the use of lakes for recreational purposes. Prevent, by any means available, spillage from entering drains or water courses.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
phosphoric acid	HIGH	HIGH
zinc sulfate monohydrate	HIGH	HIGH
copper sulfate, pentahydrate	HIGH	HIGH
magnesium sulfate, heptahydrate	HIGH	HIGH
ferrous sulfate heptahydrate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
phosphoric acid	LOW (LogKOW = -0.7699)
zinc sulfate monohydrate	LOW (BCF = 112)
copper sulfate, pentahydrate	LOW (LogKOW = -2.2002)
magnesium sulfate, heptahydrate	LOW (LogKOW = -2.2002)
ferrous sulfate heptahydrate	LOW (BCF = 52)

Mobility in soil

Mobility III Soli	
Ingredient	Mobility
phosphoric acid	HIGH (Log KOC = 1)
zinc sulfate monohydrate	LOW (Log KOC = 6.124)
copper sulfate, pentahydrate	LOW (Log KOC = 6.124)
magnesium sulfate, heptahydrate	LOW (Log KOC = 6.124)
ferrous sulfate heptahydrate	LOW (Log KOC = 6.124)

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Reuse Recycling Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sever may be subject to local laws and regulations and these should be considered first. Where in doubt contact the responsible authority. Recycle wherever possible. Consult manufacture for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followe

SECTION 14 Transport information

Labels Required



Marine Pollutant NO

HAZCHEM	2X	
Land transport (ADG)		
14.1. UN number or ID number	2922	
14.2. UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S. (contains phosphoric acid)	
14.3. Transport hazard class(es)	Class Subsidiary Hazard	8 6.1
14.4. Packing group	II	
14.5. Environmental hazard	Not Applicable	
14.6. Special precautions for	Special provisions	274
user	Limited quantity	1L

Air transport (ICAO-IATA / DGR)

14.1. UN number	2922			
14.2. UN proper shipping name	Corrosive liquid, toxic, n.o.s. * (contains phosphoric acid)			
	ICAO/IATA Class	8		
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	6.1		
class(es)	ERG Code	8P		
14.4. Packing group	II			
14.5. Environmental hazard	Not Applicable			
	Special provisions		A3 A4 A803	
	Cargo Only Packing Instructions		855	
	Cargo Only Maximum Qty / Pack		30 L	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		851	
	Passenger and Cargo Maximum Qty / Pack		1 L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y840	
	Passenger and Cargo Limited Ma	aximum Qty / Pack	0.5 L	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	2922		
14.2. UN proper shipping name	CORROSIVE LIQUID, TOXIC, N.O.S. (contains phosphoric acid)		
14.3. Transport hazard class(es)	IMDG Class8IMDG Subsidiary Hazard6.1		
14.4. Packing group	Ш		
14.5 Environmental hazard	Not Applicable		
14.6. Special precautions for user	EMS NumberF-A, S-BSpecial provisions274Limited Quantities1 L		

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
phosphoric acid	Not Available
manganese sulfate, hydrate	Not Available
zinc sulfate monohydrate	Not Available
copper sulfate, pentahydrate	Not Available
magnesium sulfate, heptahydrate	Not Available
ferrous sulfate heptahydrate	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
phosphoric acid	Not Available
manganese sulfate, hydrate	Not Available
zinc sulfate monohydrate	Not Available

Page 13 of 14 Smart Select Maxi-P +

Product name	Ship Type			
copper sulfate, pentahydrate	Not Available			
magnesium sulfate, heptahydrate	Not Available			
ferrous sulfate heptahydrate	Not Available			
SECTION 15 Regulatory information				
SECTION 15 Regulatory information				
Safety, health and environmental regulations / legislation specific for the substance or mixture				
phosphoric acid is found on the following regulatory lists				
Australia Hazardous Chemical Ir	nformation System (HCIS) - Hazardous Chemicals			
Australia Standard for the Unifor	m Scheduling of Medicines and Poisons (SUSMP) - Schedule 5			
Australian Inventory of Industrial Chemicals (AIIC)				

manganese sulfate, hydrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australian Inventory of Industrial Chemicals (AIIC)

zinc sulfate monohydrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 Australian Inventory of Industrial Chemicals (AIIC)

copper sulfate, pentahydrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 Australian Inventory of Industrial Chemicals (AIIC)

magnesium sulfate, heptahydrate is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 3 Australian Inventory of Industrial Chemicals (AIIC) FEI Equine Prohibited Substances List - Controlled Medication

FEI Equine Prohibited Substances List (EPSL)

ferrous sulfate heptahydrate is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 Australia Inventory of Industrial Chemicals (AIIC)

Additional Regulatory Information

Not Applicable

National Inventory Status

National Inventory	Status		
Australia - AIIC / Australia Non- Industrial Use	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (phosphoric acid; manganese sulfate, hydrate; zinc sulfate monohydrate; copper sulfate, pentahydrate; magnesium sulfate, heptahydrate; ferrous sulfate heptahydrate)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (ferrous sulfate heptahydrate)		
Korea - KECI	Yes		
New Zealand - NZloC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	Yes		
Vietnam - NCI	Yes		
Russia - FBEPH	Yes		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.		

SECTION 16 Other information

Revision Date	16/07/2024
Initial Date	02/04/2024

SDS Version Summary

Version	Date of Update	Sections Updated
3.1	16/07/2024	Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, Physical and chemical properties - Appearance, Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Ecological Information - Environmental, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire/fighting), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire/fighting), Firefighting measures - Fire Fighter (fire/explosion on ingredients - Ingredients, Stability and reactivity - Instability Condition, Exposure controls / personal protection (ther), Exposure controls / personal protection - Personal Protection (ther), Exposure controls / personal protection - Personal Protection (hands/feet), Accidental release measures - Spills (major), Accidental release measures - Spills (minor), Handling and storage - Storage (storage incompatibility), Handling and storage - Storage (suitable container), Transport information - Transport, Transport Information, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC TWA: Permissible Concentration-Time Weighted Average
- PC STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
 IDLH: Immediately Dangerous to Life or Health Concentrations
 ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
 EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
 PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.